



Coupling Size	Rating kW/1000 rpm	Max. Continuous Torque kNm	Peak Overload Torque kNm	Max Speed - Rpm		Weight - Transmission Unit		Weight - Unbored Hub	
				Std Hub	Large Hub	Min. DBSE Kg	Extra DBSE Kg/m	Standard Hub	Large Hub
155	300	2.9	5.8	15,300	11,300	8.6	16.2	8	21.9
185	500	4.8	9.6	12,800	10,100	13.6	21.7	13.7	34.3
209	750	7.1	14.2	11,300	9,000	19.5	27.2	19.3	46.6
235	1,050	10	20	10,100	9,000	27.9	34	31.1	45.5
262	1,500	14.3	28.6	9,000	8,200	37.5	41.8	42.2	58
288	2,000	19.1	38.2	8,200	7,400	49	49	54	77
318	2,600	24.8	49.6	7,400	-	66	60	71	-
342	3,350	32	64	6,900	-	80	68	101	-
371	4,250	40.5	81	6,300	-	105	81	135	-
417	6,010	57.3	115	5,600	-	147	101	189	-
465	8,500	81	162	5,000	-	212	132	269	-
529	13,000	124	248	4,200	-	340	169	406	-
611	17,000	162	324	3,800	-	454	203	709	-
653	21,000	200	400	3,600	-	547	234	873	-
761	36,000	344	688	3,050	-	867	328	1,423	-
834	49,000	468	936	2,800	-	1,153	403	1,934	-

\*These DBSE sizes are more readily available. Other lengths to suit specific shaft separations are available on request.

Coupling Size	D1	D2	D3 Max	D4	D5	D6 Max	D7	D8	L1	* L2 - DBSE					L3
										Min. mm	140mm	7 In.	180mm	250mm	
155	155	116	82	106	143	110	161	209	84	130	X	X	X	X	110
185	185	143	100	127	167	134	187	235	100	148	-	X	X	X	134
209	209	161	110	143	185	148	208	262	110	169	-	X	X	X	148
235	235	187	134	167	185	148	208	262	134	183	-	X	X	X	148
262	262	208	148	185	200	161	225	288	148	207	-	-	-	X	161
288	288	225	161	200	229	184	255	318	161	229	-	-	-	X	166
318	318	255	184	229	-	-	-	-	166	241	-	-	-	X	-
342	342	286	212	257	-	-	-	-	191	255	-	-	-	X	-
371	371	315	235	285	-	-	-	-	212	273	-	-	-	X	-
417	417	354	260	320	-	-	-	-	234	303	-	-	-	-	-
465	465	402	290	365	-	-	-	-	261	345	-	-	-	-	-
529	529	464	330	424	-	-	-	-	297	381	-	-	-	-	-
611	611	546	420	503	-	-	-	-	378	422	-	-	-	-	-
653	653	588	446	538	-	-	-	-	401	457	-	-	-	-	-
761	761	696	520	632	-	-	-	-	468	533	-	-	-	-	-
834	834	769	580	695	-	-	-	-	522	587	-	-	-	-	-